

SCALEOVIEW L20W-2

20 Inch LCD widescreen Display

Issue June 2007

Pages 2

An attractive price doesn't mean that you have to compromise on style or performance. The SCALEOVIEW L20W-2 widescreen display offers best performance for the office and multimedia. With its extremely slim and stylish design, the SCALEOVIEW L20W-2 fits perfectly into your office environment.

Highlights

- \$ 20-inch widescreen display for a perfect viewing experience at high resolution
- \$ Best performance to an affordable price
- \$ Very easy and comfortable to use
 - Plug & Play
 - Auto-adjust
 - Easy-to-use OSD menu

Ergonomics

- \$ Optimum flicker-free and distortion-free picture
- \$ Excellent colour purity
- \$ Well balanced brightness uniformity
- \$ Excellent high contrast:
- \$ Space saving design

Technical highlights

- \$ 20" (51.1cm) LCD widescreen display
- \$ Excellent contrast 800:1
- \$ Brightness 300 cd/m²
- \$ Fast response time (typ.) 5 ms
- \$ Internal power supply

Reliability

- \$ Low power consumption
- \$ Power management according to EPA
- \$ Guaranteed quality and stability



Visible screen diagonal	20 inch (51.1 cm)
Resolutions	
Pixels	1680 x 1050
Pixels*	1280 x 768
* expanded	
Picture size	433.44 x 270.9 mm
Colours	16.7 million
Pixel Pitch	0.258 mm
Frequencies	
Horizontal	31 - 83 kHz
Vertical	56 - 75 Hz
Brightness (typical)	300 cd/m ²
Contrast (typical)	800:1
Viewing angle (typical)	
Horizontal	160°
Vertical	160°
Response time (typical)	5 ms
Plug and Play	VESA DDC2B
Setting options	
Brightness (Back light control)	
Contrast, Volume control	
Picture position (horizontal and vertical), H-size, Phase,	
Color temperature and individual color setting	
Auto-adjust (direct access key)	
Activate factory settings	
Menu language	
OSD Language	
English, German, Spanish, French, Italian, Russian	
Base	
Tilt angle	-5°/ +20°
Audio characteristics	
Audio signal input	3.5 mm stereo phone jack
Audio output	1 W (L) + 1 W (R)

Electrical values (internal power supply)

Rated voltage	100 - 240 V
Frequency	50 - 60 Hz
Power draw	
Max.	<50 W
Stand by	< 2 W
Protection class	1

Temperatures/ dimensions/ weight

Ambient temperature (to IEC721):	
Working (recommended)	5°C to 35°C
Storage	-20°C to 60°C
Dimensions (H x W x D):	
(w/o stand)	473 x 398 x 215 mm
Weight (Monitor only)	5.4 kg

Reliability

MTBF (demonstrated)	70,000 h
Lifetime of LCD backlight	50,000 h
(brightness > 50 % of original brightness)	

Compliance with standards

Product safety	EN60950
Ergonomics	GS mark
	ISO13406-2
	(Pixel fault class II)
Radiation immunity and	CE certification according
RFI suppression	to EC Directive
	89/336/EEC
	(EN55022/B, EN55024
	EN61000-3-2/-3);
	TCO'03

Video input	1 x D-SUB
--------------------	-----------

Accessories

Power cable (1.5 m)*	For wall socket
	(Euro-Schuko-Type CEE7)
Data cable (1.5 m)*	D-SUB (15-pin)
Audio cable (1.8 m)*	3.5mm stereo phone jack
* detachable on display	

Special features

Standardized mounting interface according VESA FPMPI (100 mm) Kensington Lock

Order code	S26361-K1201-V202
	EAN: 4333643068288

